



GRAIN BODIES



SPECIFICATIONS:

Lengths	12', 14', 15', 16', 17', 18', 20', 22', 24'
Widths	96", 102"
Cross members	4" "I" beam on 12" centers
Hoist sills	(2) 6" channel
Side posts	2" x 5" HD extruded aluminum on 16" centers
Rails	HD extruded aluminum top and bottom rails
Tailgate	Top hinged with bottom latch, center grain chute
Tarp rails	2" extruded aluminum
Floor	3/16" smooth aluminum sheet
Sides	1/8" smooth aluminum sheet
Access ladder	Rear roadside
Lights	All DOT required markers and lights
Accessories	Aluminum splash-guards and mud flaps

AVAILABLE OPTIONS:

- Removable sides in lieu of permanent sides
- Custom side and/or tail gate heights
- Side hinged rear tail gate option
- Double or triple acting tailgate options
- Hydraulic assist tailgate for silage
- Cab shield
- Under body aluminum storage box

SUGGESTED BODY LENGTH TO C.A.

Body length	Truck Cab to Axle
12' - 14'	84" - 102"
15' - 16'	114" - 120"
17' - 18'	144" - 168"
20' - 22'	*
24'	*

* Check with factory sales for suggested C.A.

Units pictured may feature options not included as standard



M. H. Eby, Inc.
800/292-4752
www.mheby.com

